



VECTORPLANK

SPECIFICATIONS

SIZE	6 X 48
PLANKS/CARTON	20
SF/CARTON	40 SF
WEAR LAYER	20 MIL (0.5MM)
FINISH	URETHANE CERAMIC BEAD
INSTALLATION METHOD	GLUE DOWN
TOTAL THICKNESS	2.5 MM
WARRANTY	10 YEAR COMMERCIAL 25 YEAR - LIMITED RESIDENTIAL

ASTM TEST RESULTS

TEST	RESULT	REQUIREMENT
ASTM 1700-04 CLASSIFICATION	CLASS 111 TYPE B	
ASTM E 662-03 SMOKE DENSITY TEST (FLAMING)	PASSES	< 450
ASTM E 662-03 SMOKE DENSITY TEST (NON-FLAMING)	PASSES	< 451
ASTM F 970 STATIC LOAD	PASSES	± .005
ASTM F 1514 RESISTANCE TO HEAT	PASSES	ΔE < 8
ASTM F 1515 RESISTANCE TO LIGHT	PASSES	ΔE < 8
ASTM D 2047-04 STATIC COEFFICIENT WET	> .60	> .60
ASTM D 2047-04 STATIC COEFFICIENT DRY	> .60	> .60
ASTM E 648-08 CRITICAL RADIANT FLUX	> .60 CLASS 1	> .60
ASTM F 1914-98 RESIDUAL INDENTATION	< 8%	< 8%
ASTM F 137 FLEXIBILITY	PASSES	1 INCH MANDREL, NO CRACKING / BREAKING
ASTM F 925 CHEMICAL RESISTANCE	NO EFFECT	NO MORE THAN SLIGHT EFFECT
ASTM F 2199-09 DIMENSIONAL STABILITY	± 0.20 INCH	± 0.20 INCH
ASTM D 3884 ABRASION WHEEL	> 5000	NO MINIMUM REQUIREMENT